







zehnder

always the
best climate









Zehnder ComfoAir E350

Prices 2022 – Sales International



Comfort ventilation unit				
Product	Description	Article no.	Gross price €	Discount group
ComfoAir E350				
  Passive house certified	ComfoAir E350 comfort ventilation unit 350 m ³ /h (150 Pa) air volume flow, cross-counterflow heat exchanger with automatic 100% summer by-pass, wall-mounted or floor-mounted using an optional base mount, without three-stage switch, display operation possible Dimensions: 725 x 870 x 560 mm (W x H x D)			
	ComfoAir E 350 L with supply air connector, left ComfoAir E 350 R with supply air connector, right	471 508 115 471 508 120	2.590,50 2.590,50	C C
	ComfoAir E350 V comfort ventilation unit 350 m ³ /h (150 Pa) air volume flow, cross-counterflow heat exchanger with automatic 100% summer by-pass, wall-mounted or floor-mounted using an optional base mount, with pre-heater , without three-stage switch, display operation possible Dimensions: 725 x 870 x 560 mm (W x H x D)			
	ComfoAir E350 VL with supply air connector, left ComfoAir E350 VR with supply air connector, right	471 508 125 471 508 130	2.866,30 2.866,30	C C
	ComfoAir E350 enthalpy comfort ventilation unit 350 m ³ /h (150 Pa) air volume flow, cross-counterflow enthalpy exchanger with automatic 100% summer by-pass, wall-mounted or floor-mounted using an optional base mount, without three-stage switch, display operation possible Dimensions: 725 x 870 x 560 mm (W x H x D)			
	ComfoAir E 350 L enthalpy with supply air connector, left ComfoAir E 350 R enthalpy with supply air connector, right	471 508 220 471 508 215	3.226,70 3.226,70	C C
	ComfoAir E350 enthalpy comfort ventilation unit 350 m ³ /h (150 Pa) air volume flow, cross-counterflow enthalpy exchanger with automatic 100% summer by-pass, wall-mounted or floor-mounted using an optional base mount, with pre-heater , without three-stage switch, display operation possible Dimensions: 725 x 870 x 560 mm (W x H x D)			
	ComfoAir E 350 VL enthalpy with supply air connector, left ComfoAir E 350 VR enthalpy with supply air connector, right	471 508 230 471 508 225	3.441,90 3.441,90	C C

* Energy efficiency classes in accordance with EU Regulation no. 1254/2014.
 The energy efficiency class applied when the unit is used with manual control.
 Further information is available at www.international.zehnder-systems.com

Comfort ventilation unit				
Product	Description	Article no.	Gross price €	Discount group
ComfoAir E350 accessories				
	Three-stage switch, in-wall, with 0 position for ComfoAir E350, ComfoD 200, 180, 160	990 210 154	78,70	C
	Three-stage switch, in-wall, without 0 position for ComfoAir E350, ComfoD 200, 180, 160	659 000 120	67,00	C
	Three-stage switch, in-wall, without 0 position, with fault indication for ComfoAir E350, ComfoD 200, 180, 160	659 000 300	101,90	C
	Surface-mounted housing for three-stage switch for ComfoAir E350, ComfoD 200, 180, 160 suitable for 990 201 154	990 210 155	30,40	C
	Surface-mounted housing for three-stage switch for ComfoAir E350, ComfoD 200, 180, 160 suitable for 659 000 120 and 659 000 300	659 000 200	16,40	C
	Remote controlled RF control panel required accessories: RF board	655 000 755	120,00	C
	RF board for RF control panels	655 000 762	58,90	C
	ComfoAir E350 mounting base	471 502 008	165,60	C
	Dry siphon 5/4" for ComfoAir E350	990 201 330	54,50	C
	Filter set for ComfoAir E350 ISO Coarse ≥ 65% (G4) 2 pieces	400 502 012	44,00	B
	Filter set for ComfoAir E350 ISO Coarse ≥ 65% (G4) / ISO ePM1 ≥ 65% (F7) contents 2 pieces	400 502 013	47,60	B
	Filter set for ComfoAir E350 ISO Coarse ≥ 65% (G4) 10 pieces	400 502 014	197,00	B
	Filter set for ComfoAir E350 ISO Coarse ≥ 65% (G4) / ISO ePM1 ≥ 65% (F7) contents 10 pieces	400 502 015	230,70	B

